



NTN BEARING-SUDAMERICANA, S.A.

3HR4085T+[217-3000/1]L[H,P,SP,UP] THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 3HR4085T+[217-3000/1]L[H,P,SP,UP]

3HR4085T+[217-3000/1]L[H,P,SP,UP] Bearing
2D drawings and 3D CAD models

Days to Ship	42 Days
Rail Width W1	35 mm
Mounting Height M	40 mm
Number of blocks	3
Material	Carbon Steel
Rail Length L	217 ~ 3000 mm
Accuracy Grade	High Grade / Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	4085
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	59500
Basic Load Rating Static Rating Co(N)	91700
Allowable static moment MA(N · m)	4480
Allowable static moment MB(N · m)	4480
The outside dimension W of block	50.4 mm
The outside dimension L of block	215.9 mm
Mounting Hole Dimension S(M)	M14
The dimension L1 of blocks	158.9 mm
LM Block Surface	Not Provided



NTN BEARING-SUDAMERICANA, S.A.

Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided