



NTN BEARING-SUDAMERICANA, S.A.

3HR50105T+[276-3000/1]L[H,P,SP,UP] THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 3HR50105T+[276-3000/1]L[H,P,SP,UP]

3HR50105T+[276-3000/1]L[H,P,SP,UP]
Bearing 2D drawings and 3D CAD models

Days to Ship	42 Days
Rail Width W1	42 mm
Mounting Height M	50 mm
Number of blocks	3
Material	Carbon Steel
Rail Length L	276 ~ 3000 mm
Accuracy Grade	High Grade / Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	5010
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	96000
Basic Load Rating Static Rating Co(N)	143000
Allowable static moment MA(N · m)	8740
Allowable static moment MB(N · m)	.8.74
The outside dimension W of block	63.4 mm
The outside dimension L of block	274.5 mm
Mounting Hole Dimension S(M)	M16
The dimension L1 of bocks	197.5 mm



NTN BEARING-SUDAMERICANA, S.A.

LM Block Surface Processing	NA
LM Rail Surface Processing	NA